

Clip system:

Two which belong together like hammer and chisel: the collated FOS storm clips and the installation accelerator FOS ClipHOLSTER®.



Your benefits:



Easy removal from the packaging.



Easy removal from the strip.



Clips in easy reach.



Reduction of the installation time.



Protection from injuries.

Mechanical fixings and storm safety of covering materials for roofs and facades

We offer you the most versatile clip range for fixation and professional wind uplift safety of small-format covering materials for roofs and facades in Europe. All FOS® products are delivered by dealers and industry partners.

Our mobile roofing tools on www.fos.de assist you to work fast and easy on the topic of storm safety:

FOS ClipCHECK®

The product finder determines the suitable clips for each object.

FOS CombiCHECK®

The reverse search enables you to determine allocation of covering materials for usage with clips available in-stock.


Friedrich Ossenberg-Schule GmbH + Co KG
Amerikastraße 2
58675 Hemer
GERMANY

Tel. +49 (0) 2372. 558 99. 0
Fax +49 (0) 2372. 558 99. 99 90
info@fos.de
www.fos.de




How to use the holster?

With protective cover for
404®-2, 409®-2, 409®b-2, 461®-2



Without protective cover for
403®-2, 403®d-2, 416®-2, 453-2, 456®-2, 460®-2,
492®-2, 499-2



ClipFOS®
HOLSTER for
collated FOS® storm clips


Which FOS® clips are available collated?

Sidelock clips



409®-2 and 409®b-2

- To drive in.
- High wind uplift resistance.
- Drive-in aid and nail tip.
- Ring shanked.
- Deliverable in round and angular hook forms.
- Deliverable in different lengths.
- Deliverable in stainless steel and ZIAL®.



456®-2

- To mount on.
- High wind uplift resistance.
- Pre-installation and replacement of single tiles possible.
- Special interlocking at roof batten ensures secure hold.
- Deliverable in round and angular hook forms.
- Deliverable in different lengths.
- Deliverable in stainless steel and ZIAL®.



499-2

- To mount on.
- Deliverable in round and angular hook forms.
- Deliverable in different lengths.
- Deliverable in stainless steel and ZIAL®.

Head-sidelock clips




416®-2

- To to mount on.
- Suitable for standard wooden battens.
- Tool-free installation.
- Deliverable in different lengths.
- Deliverable in stainless steel and ZIAL®.



453-2


- To nail.
- High wind uplift resistance.
- Drive-in aid.
- Ring shanked.
- Deliverable in different versions.
- Deliverable in stainless steel.



492®-2

- To mount on.
- Is fixing both the head and the side fold of roof tiles without a fourfold covering in the 4-tile corner.
- Deliverable in different versions.
- Deliverable in stainless steel and ZIAL®.

Head-foot clips



403®-2

- To mount on.
- Can be used in a variety of ways as installation aid at connections and terminations.
- Suitable for cut pieces at hip and as replacement nibs in case of missing hanging nibs.
- Deliverable in different versions.
- Deliverable in stainless steel.



403®d-2


- To drive in.
- Can be used in a variety of ways as installation aid at connections and terminations, as replacement nibs in case of missing hanging nibs and for cut pieces at hip.
- Drive-in aid.
- Replacement of single tiles possible.
- Deliverable in different versions.
- Deliverable in stainless steel.



Quick installation, easy handling and high-quality materials are important.

Collated clips guarantee time savings and durability for storm safety on pitched roofs.

Slate and tile hooks



404®-2

- To drive in.
- Drive-in aid.
- Ring shanked.
- Smoothed end of the clip.
- Deliverable in different lengths.
- Deliverable in stainless steel polished and in varnished black.



460®-2

- To mount on.
- Smoothed end of the clip.
- Deliverable in different lengths.
- Deliverable in stainless steel polished and in varnished black.



461®-2

- To drive in.
- Can be used to secure natural slate and fibre cement tiles on facades.
- Drive-in aid.
- Ring shanked.
- Smoothed end of the clip.
- Deliverable in different lengths.
- Deliverable in stainless steel polished and in varnished black.