

Mechanical fixings and storm safety of covering materials for roofs and facades

We offer you the most versatile clip range for fixing and professional wind uplift safety of small-format covering materials for roofs and facades in Europe. All FOS products are delivered by dealers and industry partners.

Our online roofing tools on www.fos.de assist you to work fast and easy on the topic of storm safety:

FOS ClipCHECK

Our new product locator determines the perfect clip for your object with a few clicks.

FOS CombiCHECK

The reverse search enables you to determine allocation of covering materials for usage with clips available in-stock.

Friedrich Ossenberg-Schule GmbH + Co KG
 Amerikastraße 2
 58675 Hemer
 GERMANY

Tel. +49 (0) 2372. 558 99. 0
 Fax +49 (0) 2372. 558 99. 99 90
info@fos.de
www.fos.de



> Professional storm protection for roof tiles

FOS ridge clips at a glance

Color variations:



Material variants:



Enquiries:


What must be considered when using FOS ridge clips following the technical regulations of the German roofer confederation?

The ridge tiles must withstand a windload of 0.60 kN per meter.

Clips and screws must be corrosion-resistant.

Screws have to be at least 4.5 mm thick and provide a minimum penetration of 24 mm into the substructure.

Fixing the ridge clip:



1. with a screw through the ridge tile
2. with a screw into the substructure



Conclusion:

Your benefits from using FOS ridge clips:

- ✓ Wide range of shapes
- ✓ Wide range of colours
- ✓ Allocations for all common ridge- and hip tiles on our website: www.fos.de
- ✓ Small packaging units
- ✓ Quality Made in Germany

Reliable uplift resistance against wind load. Almost invisible on the roof.

Installation

FOS ridge clips allow a permanently secure connection of a hip or ridge tile to the substructure. It secures continues air circulation of the ridge.

Ridge clips, available in various forms, enable a quick and simple assembly of the ridge or hip on the roof.



Large variety of ridge clip shapes

A large variety of shapes enables us to offer a suitable clip for almost any ridge or hip tiles (clay or concrete) on the market. The correct FOS ridge clips allocations for ridge- and hip tiles can easily be done on our website www.fos.de.



470°-083

470°-200

Large variety of colours

Due to a wide variety of colours FOS ridge clips can blend in with many respective ridge tile colour. Ridge clips in the colour red, brown and black are in stock. The colours deep black, zinc grey, dark green, light green, dark blue, light blue, red brown and sand yellow have short delivery times.

On request, we are able to provide ridge clips in any desired colour.

Additional, we offer FOS ridge clips in stainless steel.

